

**Ecobrite Super Silex Liquid****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Ecobrite Super Silex Liquid  
Product code : 115611E  
Use of the Substance/Mixture : Laundry detergent  
Substance type: : Mixture

**For professional users only.**

Product dilution information : No dilution information provided.

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laundry detergent. Automatic process  
Recommended restrictions on use : Reserved for industrial and professional use.

**1.3 Details of the supplier of the safety data sheet**

Company : Ecolab Ltd.  
PO Box 11; Winnington Avenue  
Northwich, Cheshire, United Kingdom CW8 4DX  
+353 (0)1 276 3500  
ccs@ecolab.com

**1.4 Emergency telephone number**

Emergency telephone number : +353766805288  
+32-(0)3-575-5555 Trans-European  
Poison Information Centre telephone number : For medical professionals only:  
+353 (0)1 837 9964 (8am-10pm)

Date of Compilation/Revision : 23.03.2020  
Version : 2.0

**Section: 2. HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Skin irritation, Category 2 H315  
|| Serious eye damage, Category 1 H318

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

**Ecobrite Super Silex Liquid**

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H315  
H318

Causes skin irritation.

Causes serious eye damage.

Precautionary Statements

: **Prevention:**  
P280

Wear protective gloves/ eye protection/ face protection.

**Response:**P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:  
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt  
Alcohols, C13-15, branched and linear, ethoxylated

**2.3 Other hazards**

None known.

**Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	68411-30-3 270-115-0 01-2119489428-22	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 5 - < 10
Alcohols, C13-15, branched and linear, ethoxylated	157627-86-6 POLYMER	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318 Chronic aquatic toxicity Category 3; H412	>= 5 - < 10
fatty acids, coco, compds. with triethanolamine	61790-64-5 263-155-5 REACH EXEMPTED	Eye irritation Category 2; H319	>= 5 - < 10
Fatty acids, coco, sodium salts	61789-31-9 263-050-4 EXEMPTED	Eye irritation Category 2; H319	>= 5 - < 10
Alcohols, C13, branched, ethoxylated	69011-36-5 POLYMER	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318	>= 2.5 - < 3
sodium hydroxide	1310-73-2 215-185-5 01-2119457892-27	Skin corrosion Category 1A; H314 Corrosive to metals Category 1; H290	>= 0.5 - < 1
Substances with a workplace exposure limit :			

**Ecobrite Super Silex Liquid**

Propylene glycol	57-55-6 200-338-0 01-2119456809-23	Not Classified;	>= 5 - < 10
------------------	--	-----------------	-------------

For the full text of the H-Statements mentioned in this Section, see Section 16.

**Section: 4. FIRST AID MEASURES**

**4.1 Description of first aid measures**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Get medical attention if irritation develops and persists.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

**4.2 Most important symptoms and effects, both acute and delayed**

See Section 11 for more detailed information on health effects and symptoms.

**4.3 Indication of immediate medical attention and special treatment needed**

- Treatment : Treat symptomatically.

**Section: 5. FIREFIGHTING MEASURES**

**5.1 Extinguishing media**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

**5.2 Special hazards arising from the substance or mixture**

- Specific hazards during firefighting : Not flammable or combustible.
- Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides  
nitrogen oxides (NOx)  
Sulphur oxides

**5.3 Advice for firefighters**

- Special protective equipment for firefighters : Use personal protective equipment.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

**Ecobrite Super Silex Liquid**

**Section: 6. ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures**

- Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
- Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

**6.2 Environmental precautions**

- Environmental precautions : Do not allow contact with soil, surface or ground water.

**6.3 Methods and materials for containment and cleaning up**

- Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

**6.4 Reference to other sections**

- See Section 1 for emergency contact information.  
For personal protection see section 8.  
See Section 13 for additional waste treatment information.

**Section: 7. HANDLING AND STORAGE**

**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid contact with skin and eyes. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

**7.2 Conditions for safe storage, including any incompatibilities**

- Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : 0 °C to 40 °C

**Ecobrite Super Silex Liquid**

**7.3 Specific end uses**

Specific use(s) : Laundry detergent. Automatic process

**Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Propylene glycol	57-55-6	OELV - 8 hrs (TWA) (particles)	10 mg/m3	IR_OEL
Further information		Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used		
		OELV - 8 hrs (TWA) (total (vapour and particles))	150 ppm 470 mg/m3	IR_OEL
Further information		Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit value should be used		
sodium hydroxide	1310-73-2	OELV - 15 min (STEL)	2 mg/m3	IR_OEL

**DNEL**

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 85 mg/cm2
	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 85 mg/cm2
	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 6 mg/m3
	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 6 mg/m3
Propylene glycol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 168 mg/m3
	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m3
	:	End Use: Consumers Exposure routes: Inhalation

**Ecobrite Super Silex Liquid**

	<p>Potential health effects: Long-term systemic effects Value: 50 mg/m<sup>3</sup></p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 10 mg/m<sup>3</sup></p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 213 mg/cm<sup>2</sup></p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 85 ppm</p>
sodium hydroxide	<p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m<sup>3</sup></p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m<sup>3</sup></p>

**PNEC**

benzenesulfonic acid, C10-13- alkyl derivs., sodium salt	<p>: Fresh water Value: 0.268 mg/l</p> <p>Marine water Value: 0.0268 mg/l</p> <p>Intermittent use/release Value: 0.0167 mg/l</p> <p>Fresh water sediment Value: 8.1 mg/kg</p> <p>Marine sediment Value: 8.1 mg/kg</p> <p>Sewage treatment plant Value: 3.43 mg/l</p>
Propylene glycol	<p>: Fresh water Value: 260 mg/l</p> <p>Marine water Value: 26 mg/l</p> <p>Intermittent use/release Value: 183 mg/l</p>

**Ecobrite Super Silex Liquid**

	Fresh water sediment Value: 572 mg/kg  Marine sediment Value: 57.2 mg/kg  Sewage treatment plant Value: 20000 mg/l  Soil Value: 50 mg/kg
--	--

**8.2 Exposure controls**

**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Individual protection measures**

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles  
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection  
Gloves  
Nitrile rubber  
butyl-rubber  
Breakthrough time: 1 – 4 hours  
Minimum thickness for butyl-rubber 0.3 mm for nitrile rubber 0.2 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

**Environmental exposure controls**

General advice : Consider the provision of containment around storage vessels.

**Ecobrite Super Silex Liquid**

**Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

Appearance	: liquid
Colour	: light green
Odour	: Perfumes, fragrances
pH	: 8.0 - 8.7, 100 %
Flash point	: Not applicable.
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: Not applicable and/or not determined for the mixture
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 1.03 - 1.05
Water solubility	: soluble
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: 173.389 mm <sup>2</sup> /s (40 °C)
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

**9.2 Other information**

Not applicable and/or not determined for the mixture

**Section: 10. STABILITY AND REACTIVITY**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.



**Ecobrite Super Silex Liquid**

**10.3 Possibility of hazardous reactions**

No dangerous reaction known under conditions of normal use.

**10.4 Conditions to avoid**

None known.

**10.5 Incompatible materials**

None known.

**10.6 Hazardous decomposition products**

Depending on combustion properties, decomposition products may include following materials:  
Carbon oxides  
nitrogen oxides (NO<sub>x</sub>)  
Sulphur oxides

**Section: 11. TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects**

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

**Product**

- Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
- Acute inhalation toxicity : There is no data available for this product.
- Acute dermal toxicity : There is no data available for this product.
- Skin corrosion/irritation : There is no data available for this product.
- Serious eye damage/eye irritation : There is no data available for this product.
- Respiratory or skin sensitization : There is no data available for this product.
- Carcinogenicity : There is no data available for this product.
- Reproductive effects : There is no data available for this product.
- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : There is no data available for this product.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

**Components**

**Ecobrite Super Silex Liquid**

Acute oral toxicity : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt  
LD50 rat: 1,080 mg/kg

fatty acids, coco, compds. with triethanolamine  
LD50 rat: 6,400 mg/kg

Alcohols, C13, branched, ethoxylated  
LD50 rat: > 500 mg/kg

Propylene glycol  
LD50 rat: 22,000 mg/kg

**Components**

Acute inhalation toxicity : Propylene glycol  
4 h LC50 rat: > 158.5 mg/l  
Test atmosphere: dust/mist

**Potential Health Effects**

Eyes : Causes serious eye damage.

Skin : Causes skin irritation.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

**Experience with human exposure**

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Irritation

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

**Section: 12. ECOLOGICAL INFORMATION**

**12.1 Ecotoxicity**

Environmental Effects : This product has no known ecotoxicological effects.

**Product**

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

**Components**

Toxicity to fish : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt  
96 h LC50 *Lepomis macrochirus* (Bluegill sunfish): 1.67 mg/l

Alcohols, C13, branched, ethoxylated

**Ecobrite Super Silex Liquid**

96 h LC50 Fish: 3 mg/l

Propylene glycol  
96 h LC50: > 10,000 mg/l

**Components**

Toxicity to daphnia and other aquatic invertebrates : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt  
48 h LC50 Daphnia magna (Water flea): 2.4 mg/l

Alcohols, C13, branched, ethoxylated  
48 h EC50 Daphnia magna (Water flea): 1.5 mg/l

sodium hydroxide  
48 h EC50: 40 mg/l

Propylene glycol  
48 h EC50: 18,340 mg/l

**Components**

Toxicity to algae : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt  
96 h EC50 Pseudokirchneriella subcapitata (green algae): 29 mg/l

Propylene glycol  
96 h EC50: 19,000 mg/l

**12.2 Persistence and degradability**

**Product**

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

**Components**

Biodegradability : benzenesulfonic acid, C10-13- alkyl derivs., sodium salt  
Result: Readily biodegradable.

Alcohols, C13-15, branched and linear, ethoxylated  
Result: Readily biodegradable.

fatty acids, coco, compds. with triethanolamine  
Result: Readily biodegradable.

Alcohols, C13, branched, ethoxylated  
Result: Biodegradable

sodium hydroxide  
Result: Not applicable - inorganic

Propylene glycol  
Result: Readily biodegradable.

**12.3 Bioaccumulative potential**

no data available

**12.4 Mobility in soil**

**Ecobrite Super Silex Liquid**

no data available

**12.5 Results of PBT and vPvB assessment**

**Product**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

no data available

**Section: 13. DISPOSAL CONSIDERATIONS**

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**13.1 Waste treatment methods**

Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

**Section: 14. TRANSPORT INFORMATION**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

**Land transport (ADR/ADN/RID)**

14.1 UN number : Not dangerous goods  
14.2 UN proper shipping name : Not dangerous goods  
14.3 Transport hazard class(es) : Not dangerous goods  
14.4 Packing group : Not dangerous goods  
14.5 Environmental hazards : Not dangerous goods  
14.6 Special precautions for user : Not dangerous goods

**Ecobrite Super Silex Liquid**

**Air transport (IATA)**

14.1 UN number : Not dangerous goods  
14.2 UN proper shipping name : Not dangerous goods  
14.3 Transport hazard class(es) : Not dangerous goods  
14.4 Packing group : Not dangerous goods  
14.5 Environmental hazards : Not dangerous goods  
14.6 Special precautions for user : Not dangerous goods

**Sea transport (IMDG/IMO)**

14.1 UN number : Not dangerous goods  
14.2 UN proper shipping name : Not dangerous goods  
14.3 Transport hazard class(es) : Not dangerous goods  
14.4 Packing group : Not dangerous goods  
14.5 Environmental hazards : Not dangerous goods  
14.6 Special precautions for user : Not dangerous goods  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

**Section: 15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Anionic surfactants, Non-ionic surfactants, Soap  
Other constituents: Enzymes, Optical brighteners, Perfumes  
Preservation agents:  
2-phenoxyethanol  
Allergens:  
Benzyl salicylate  
Hexyl cinnamal  
Amyl cinnamal  
Alpha-Isomethyl Ionone

**National Regulations**

**Take note of Dir 94/33/EC on the protection of young people at work.**

Other regulations : Safety, Health and Welfare at Work Act, 2005  
European Communities (Classification, Packaging, Labelling and Notification of Dangerous Preparations) Regulations 1995. (S.I. 272 of 1995) as amended

**15.2 Chemical Safety Assessment**

No Chemical Safety Assessment has been carried out on the product.

**Ecobrite Super Silex Liquid****Section: 16. OTHER INFORMATION****Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Skin irritation 2, H315	Calculation method
Serious eye damage 1, H318	Calculation method

**Full text of H-Statements**

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

**Ecobrite Super Silex Liquid**

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Annex: Exposure Scenarios**

**Exposure Scenario: Laundry detergent. Automatic process**

Life Cycle Stage : Use at industrial sites  
Product category : **PC35** Washing and cleaning products (including solvent based products)

**Contributing scenario controlling environmental exposure for:**

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles  
Daily amount per site : 50 kg  
Type of Sewage Treatment Plant : Municipal sewage treatment plant

**Contributing scenario controlling worker exposure for:**

Process category : **PROC8b** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities  
Exposure duration : 60 min  
Operational conditions and risk management measures : Indoor  
Local Exhaust Ventilation is not required  
General ventilation Ventilation rate per hour 1  
Skin Protection : Yes: See Section 8  
Respiratory Protection : No

**Contributing scenario controlling worker exposure for:**

Process category : **PROC2** Use in closed, continuous process with occasional controlled exposure  
Exposure duration : 480 min

**Ecobrite Super Silex Liquid**

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : No

Respiratory Protection : No