

Oasis Pro Toilet**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Oasis Pro Toilet
UFI : A51M-5HGC-KC0U-V9KG
Product code : 116792E
Use of the Substance/Mixture : Toilet Bowl Cleaner
Substance type: : Mixture

For professional users only.

Product dilution information : 1.0 % - 8.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Sanitary cleaner. Manual process
Recommended restrictions : Reserved for industrial and professional use.
on use

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Limited
Forest Park
Mullingar Industrial Estate, Mullingar Co. Westmeath Ireland +353
1 276 3500
infoireland@ecolab.com

Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+353 (0)1 276 3500
ccs@ecolab.com

1.4 Emergency telephone number

Poison Information Centre : Poisons Information: For information or to report a poisoning
telephone number incident contact The National Poisons Information Centre (01
8092166)

Date of Compilation/Revision : 02.06.2022
Version : 1.3

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Oasis Pro Toilet

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD

Corrosive to metals, Category 1	H290
Skin corrosion, Category 1	H314
Serious eye damage, Category 1	H318


Product AT USE DILUTION

Not a hazardous substance or mixture., The classification of this product is based on toxicological assessment.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Phosphoric acid
Fatty alcohol ethoxylates > 5EO

Product AT USE DILUTION

Not a hazardous substance or mixture.

Additional Labelling:

Product AS SOLD

Special labelling of certain mixtures : Not applicable.

Product AT USE DILUTION

Special labelling of certain mixtures : Safety data sheet available on request.

2.3 Other hazards

Product AS SOLD

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Oasis Pro Toilet

Product AT USE DILUTION

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Product AS SOLD

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Phosphoric acid	7664-38-2 231-633-2 01-2119485924-24	Skin corrosion Category 1B; H314 Corrosive to metals Category 1; H290 Skin corrosion Category 1B H314 25 - 100 % Skin irritation Category 2 H315 10 - < 25 % Eye irritation Category 2 H319 10 - < 25 %	>= 50 - <= 100
Alkylamineoxides	61791-46-6 263-179-6	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400	>= 5 - < 10
Diethylene Glycol	111-46-6 203-872-2 01-2119457857-21	Acute toxicity Category 4; H302 Specific target organ toxicity - repeated exposure Category 2; H373	>= 2.5 - < 5
Sodium Xylenesulfonate	1300-72-7 215-090-9 01-2119513350-56	Eye irritation Category 2; H319	>= 1 - < 2.5
Alcohols, C13, branched, ethoxylated	69011-36-5 POLYMER	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318	>= 1 - < 2.5
Dodecyldimethylamine oxide	1643-20-5 216-700-6 01-2120068065-58	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400 Chronic aquatic toxicity Category 2; H411	>= 0.5 - < 1

Product AT USE DILUTION

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Phosphoric acid	7664-38-2 231-633-2 01-2119485924-24	Skin corrosion Category 1B; H314 Corrosive to metals Category 1; H290 Skin corrosion Category 1B H314 25 - 100 % Skin irritation Category 2 H315 10 - < 25 %	>= 3 - < 5

Oasis Pro Toilet

		Eye irritation Category 2 H319 10 - < 25 %	
Alkylamineoxides	61791-46-6 263-179-6	Acute toxicity Category 4; H302 Skin irritation Category 2; H315 Serious eye damage Category 1; H318 Acute aquatic toxicity Category 1; H400	>= 0.25 - < 0.5
Substances with a workplace exposure limit :			
Diethylene Glycol	111-46-6 203-872-2 01-2119457857-21	Acute toxicity Category 4; H302 Specific target organ toxicity - repeated exposure Category 2; H373	>= 0.1 - < 0.25

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

Product AS SOLD

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.

Product AT USE DILUTION

- In case of eye contact : Rinse with plenty of water.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local

Oasis Pro Toilet

circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus
metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : Do not allow contact with soil, surface or ground water.

Oasis Pro Toilet

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Use only with adequate ventilation. Wash hands thoroughly after handling. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Oasis Pro Toilet

Product AS SOLD

Requirements for storage areas and containers : Keep away from strong bases. Absorb spillage to prevent material damage. Keep out of reach of children. Keep container tightly closed. Keep only in original packaging. Store in suitable labeled containers.

Storage temperature : 0 °C to 40 °C

Packaging material : Suitable material: Plastic material
 Unsuitable material: Mild steel, Aluminium

Product AT USE DILUTION

Requirements for storage areas and containers : Keep away from strong bases. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses

Product AS SOLD

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Product AS SOLD

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Phosphoric acid	7664-38-2	OELV - 8 hrs (TWA)	1 mg/m3	IR_OEL
		OELV - 15 min (STEL)	2 mg/m3	IR_OEL
Diethylene Glycol	111-46-6	OELV - 8 hrs (TWA)	23 ppm 100 mg/m3	IR_OEL

DNEL

Phosphoric acid	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 2 mg/m3 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3 End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 0.73 mg/m3
-----------------	---	---

8.2 Exposure controls

Product AS SOLD

Appropriate engineering controls

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

Oasis Pro Toilet

below occupational exposure standards.

Individual protection measures

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
- Eye/face protection (EN 166) : Safety goggles
Face-shield
- Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Product AT USE DILUTION

Appropriate engineering controls

- Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.
- Eye/face protection (EN 166) : No special protective equipment required.
- Hand protection (EN 374) : No special protective equipment required.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU

Oasis Pro Toilet

requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

	Product AS SOLD	Product AT USE DILUTION
Physical state	: liquid	liquid
Colour	: clear, dark blue	blue
Odour	: pleasant	odourized
pH	: 0.1 - 0.5, 100 %	1.2 - 1.4
Particle characteristics		
Assessment	: not applicable	not applicable
Particle size	: not applicable	not applicable
Particle Size Distribution	: not applicable	not applicable
Dustiness	: not applicable	not applicable
Specific surface area	: not applicable	not applicable
Surface charge/Zeta potential	: not applicable	not applicable
Shape	: not applicable	not applicable
Crystallinity	: not applicable	not applicable
Surface treatment /Coatings	: not applicable	not applicable
Flash point	: Not applicable., Does not sustain combustion.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Boiling point, initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Density and / or relative density	: 1.4 - 1.5	
Water solubility	: soluble	
Solubility in other solvents	: Not applicable and/or not determined for the mixture	

Oasis Pro Toilet

Partition coefficient: n-octanol/water (log value)	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Decomposition products may include the following materials:

Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Oasis Pro Toilet

- Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
- Acute inhalation toxicity : There is no data available for this product.
- Acute dermal toxicity : There is no data available for this product.
- Respiratory or skin sensitization : There is no data available for this product.
- Carcinogenicity : There is no data available for this product.
- Reproductive effects : There is no data available for this product.
- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : There is no data available for this product.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

Components

- Acute oral toxicity : Phosphoric acid LD50 rat: > 2,600 mg/kg
Alkylamineoxides LD50 rat: 1,041 mg/kg
Sodium Xylenesulfonate LD50 rat: > 7,000 mg/kg
Alcohols, C13, branched, ethoxylated LD50 rat: > 500 mg/kg
Dodecyldimethylamine oxide LD50 rat: 1,064 mg/kg

Components

- Acute inhalation toxicity : Phosphoric acid 4 h LC50 rat: 0.962 mg/l
Test atmosphere: dust/mist

Components

- Acute dermal toxicity : Phosphoric acid LD50 rabbit: > 2,000 mg/kg
Diethylene Glycol LD50 rabbit: 13,300 mg/kg

Potential Health Effects

Product AS SOLD

- Eyes : Causes serious eye damage.
- Skin : Causes severe skin burns.
- Ingestion : Causes digestive tract burns.
- Inhalation : Harmful if inhaled. May cause nose, throat, and lung irritation.
- Chronic Exposure : Health injuries are not known or expected under normal use.

Oasis Pro Toilet

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.
Skin : Health injuries are not known or expected under normal use.
Ingestion : Health injuries are not known or expected under normal use.
Inhalation : Health injuries are not known or expected under normal use.
Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion
Skin contact : Redness, Pain, Corrosion
Ingestion : Corrosion, Abdominal pain
Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : No symptoms known or expected.
Skin contact : No symptoms known or expected.
Ingestion : No symptoms known or expected.
Inhalation : No symptoms known or expected.

11.2 Information on other hazards

Further information : no data available

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Product AS SOLD

Environmental Effects : This product has no known ecotoxicological effects.

Product AT USE DILUTION

Environmental Effects : Harmful to aquatic life.

Product AS SOLD

Product

Toxicity to fish : no data available
Toxicity to daphnia and other aquatic invertebrates : no data available
Toxicity to algae : no data available

Components

Toxicity to fish : Alkylamineoxides96 h LC50 Fish: 1 mg/l
Diethylene Glycol96 h LC50 Pimephales promelas (fathead minnow): 75,200 mg/l

Oasis Pro Toilet

Alcohols, C13, branched, ethoxylated 96 h LC50 Fish: 3 mg/l

Dodecyldimethylamine oxide 96 h LC50 *Lepomis macrochirus* (Bluegill sunfish): 31.8 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Phosphoric acid 48 h EC50 *Daphnia magna* (Water flea): > 100 mg/l

Diethylene Glycol 24 h EC50 *Daphnia magna* (Water flea): > 10,000 mg/l

Alcohols, C13, branched, ethoxylated 48 h EC50 *Daphnia magna* (Water flea): 1.5 mg/l

Dodecyldimethylamine oxide 48 h EC50 *Daphnia magna* (Water flea): 3.9 mg/l

Components

Toxicity to algae : Phosphoric acid 72 h EC50 *Desmodesmus subspicatus* (green algae): > 100 mg/l

Diethylene Glycol 96 h EC50: 9,362 mg/l

Sodium Xylenesulfonate 96 h EC50: 230 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Phosphoric acid Result: Not applicable - inorganic

Alkylamine oxides Result: Readily biodegradable.

Diethylene Glycol Result: Readily biodegradable.

Sodium Xylenesulfonate Result: Biodegradable

Alcohols, C13, branched, ethoxylated Result: Biodegradable

Dodecyldimethylamine oxide Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Oasis Pro Toilet

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

12.7 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

- Product : Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations
Dispose of wastes in an approved waste disposal facility.
- Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Guidance for Waste Code selection : Inorganic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Product AT USE DILUTION

- Product : Do not contaminate storm water drains, natural waterways or soil with chemical or used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations
Dispose of wastes in an approved waste disposal facility.
- Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.

Section: 14. TRANSPORT INFORMATION

Oasis Pro Toilet

Product AS SOLD

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- 14.1 UN number or ID number : 1805
- 14.2 UN proper shipping name : PHOSPHORIC ACID SOLUTION
- 14.3 Transport hazard class(es) : 8
- 14.4 Packing group : III
- 14.5 Environmental hazards : No
- 14.6 Special precautions for user : None

Air transport (IATA)

- 14.1 UN number or ID number : 1805
- 14.2 UN proper shipping name : Phosphoric acid, solution
- 14.3 Transport hazard class(es) : 8
- 14.4 Packing group : III
- 14.5 Environmental hazards : No
- 14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

- 14.1 UN number or ID number : 1805
- 14.2 UN proper shipping name : PHOSPHORIC ACID SOLUTION
- 14.3 Transport hazard class(es) : 8
- 14.4 Packing group : III
- 14.5 Environmental hazards : No
- 14.6 Special precautions for user : None
- 14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Non-ionic surfactants
less than 5 %: Anionic surfactants, Polycarboxylates
Other constituents: Perfumes
Allergens:
Hexyl cinnamalLimoneneCoumarin

- Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major- : Not applicable.

Oasis Pro Toilet

accident hazards involving dangerous substances.

Candidate List of Substances : Not applicable.
of Very High Concern for Authorisation

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : Safety, Health and Welfare at Work Act, 2005
European Communities (Classification, Packaging, Labelling and Notification of Dangerous Preparations) Regulations 1995. (S.I. 272 of 1995) as amended

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Corrosive to metals 1, H290	Calculation method
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment

Full text of H-Statements

H290 May be corrosive to metals.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -

Oasis Pro Toilet

International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Sanitary cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers
Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems
Daily amount per site : 7.5 kg
Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Oasis Pro Toilet

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8