

Industrial / Spectacles / 506 UP

506 UP - Solar G15

Code: 506U.04.04.05 Date: 01-03-23 1/2

506 UP presents technical and aesthetic improvements. The panoramic and wrapping lens is available with Vanguard Plus coating for superior performance in all conditions. The temples with rubber tips and adjustable in length and inclination, the total adaptability of the nosepad and the new range of vibrant colors allow a high degree of customisation of the device.



Frame mark (EU)	Lens mark (EU)	Frame technology
506U U 166 FT CE	2C-3/5-3.1 U 1 FT CE	Nose pad set-up, Adjustment of temples in length, Adjustment of temples in inclination, Rubber Terminal
Conditions of use	Lens technology	Lens color
High brightness	Anti-Scratch, UV400	Green
Lens material	Frame color	Standards
Polycarbonate	Black/Green	EN166, EN170, EN172
Scale number	Mechanical resistance	Optional requirements
(2C-3), (5-3.1)	Low energy impact (F)	Protection against high speed particles at extreme temperatures -5°/+55° C (T)
Optical class	Weight	
Optical class (1)	25g	

Industrial / Spectacles / 506 UP

>> https://www.univetsafety.com/en/products/safety/spectacles/506-up/506-up-solar-g15/



01.

TEMPLES ADJUSTABLE IN LENGTH AND INCLINATION

02.

OPTIMAL COMFORT AND FIT THANKS TO THE SOFT ADJUSTABLE NOSE PAD 03.

PANORAMIC AND WRAPAROUND LENS FOR A BETTER SIDE PROTECTION

04.

SOFT TERMINAL TIPS TO ELIMINATE LOCAL PRESSURE

Attention! Any images on this page illustrate the frame technologies of the product family in question and may represent frame and lens colours that do not correspond to the product code of the following sheet.