

2015/830

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)

SAFETY DATA SHEET

Domestos Zero Limescale Professional

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	:	Domestos Zero Limescale Professional
Product code	:	200000118398;8314328_S, 32962438
Product description	:	Limescale Remover for Toilets
Product type	:	gel
Other means of identification	:	Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses Consumer and professional uses

1.3 Details of the supplier of the safety data sheet

Unilever Ireland Limited 20 Riverwalk National Digital Park Citywest Business Campus Dublin 24 IRELAND Eire 1850 388 399

e-mail address of person : unileversds@unileverconsumerlink.co.uk responsible for this SDS

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830
Page:2/30

National contact

Not available.

1.4 Emergency telephone number

National advisory body/Poison Center

Version: 1.0	Date of issue/Date of revision:	05.11.2020	Date of previous issue:	00.00.0000
Telephone number	Member 7 days a	rs of Public: +35 a week)	ation Centre of Ireland 3 (01) 809 2166. (8.00 : +353 (01) 809 2566 (2	
<u>Supplier</u>				
Telephone number	: Eire 18:	50 388 399		
Hours of operation	: -			
Information limitation	ns : Not ava	ilable.		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Met. Corr. 1 H290 Skin Corr./Irrit. 1 H314 Aquatic Chronic 3 H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity

: Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 0 %

Ingredients of unknown : Percentage of the mixture consisting of ingredient(s) of unknown **ecotoxicity** hazards to the aquatic environment: 0 %

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

1.0



Danger

Signal word

Version:

Date of issue/Date of revision:

05.11.2020



Hazard statements	:	May be corrosive to metals. Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects.
Precautionary statements		
General	:	P102 Keep out of reach of children.
Prevention	:	P273 Avoid release to the environment.P234 Keep only in original packaging.P280 Wear protective gloves and eye/face protection.
Response	:	 P351 Rinse cautiously with water for several minutes. P330 Rinse mouth. P338 Remove contact lenses, if present and easy to do. Continue rinsing. P303 IF ON SKIN (or hair): P353 Rinse skin with water [or shower]. P310 Immediately call a POISON CENTER or doctor/physician. P301 IF SWALLOWED: P361 Remove/Take off immediately all contaminated clothing. P305 IF IN EYES: P331 Do NOT induce vomiting.
Storage	:	Not applicable.
Disposal	:	Dispose of used up container in accordance with local regulations.
Hazardous ingredients	:	Hydrochloric acid Sulfamic Acid PEG-2 Oleamine
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirements		
Containers to be fitted with child resistant fastenings Tactile warning of danger	l-: :	Yes, applicable. Yes, applicable.
2.3 Other hazards		

Date of issue/Date of revision: 05.11.2020

Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.
Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.

Other hazards which do not result : None known. **in classification**

SECTION 3: Composition/information on ingredients

Substance/mixture

Mixture

:

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Hydrochloric acid	RRN : 012119484862- 27 EC : 231-595-7 CAS : 7647-01-0 Index : 017- 00201-X	>= 5 - < 10	Skin Corr./Irrit. 1B, H314 25 - 100 % StotSe 3, H335 10 - 100 % Skin Corr./Irrit. 2, H315 10 - 25 % Eye Dam./Irrit. 2, H319 10 - 25 %	
Sulfamic Acid	RRN : 012119846728- 23 EC : 226-218-8 CAS : 5329-14-6 Index : 016-026- 00-0	>= 5 - < 10	Skin Corr./Irrit. 2, H315 Eye Dam./Irrit. 2, H319 Aquatic Chronic 3, H412	
PEG-2 Oleamine	EC : 500-048-7 CAS : 26635-938	>= 1 - < 3	Acute Tox. 4, H302 Skin Corr./Irrit. 1B, H314 Aquatic Acute 1, H400 M: 1 Aquatic Chronic 1, H410 M: 1	

Cetrimonium Chloride	RRN : 012119970558- 23 EC : 203-928-6 CAS : 112-02-7	>= 0,1 - < 1	Skin Corr./Irrit. 1C, H314 Aquatic Acute 1, H400 M: 10 Acute Tox. 4, H302 Eye Dam./Irrit. 1, H318 Acute Tox. 3, H311 Aquatic Chronic 1, H410 M: 1
			1

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

For confidentiality reasons, the levels of components listed in Section 3 are given in percentage bands. The bandings do not reflect potential variation in composition of this formulation, but are used simply to mask the exact component levels, which we consider to be proprietary information. The classification given in Section 2 and 15 reflects the exact composition of this mixture.

* exempted according to REACH Art. 2(7) and Annex V; Each starting material of the ionic mixture is registered, if required

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Get medical attention immediately. Check for and remove any contact lenses. Call a poison center or physician. Chemical burns must be treated promptly by a physician. Continue to rinse for at least 10 minutes.

Inhalation	:	Get medical attention immediately. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Loosen tight clothing such as a collar, tie, belt or waistband. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Maintain an open airway. Call a poison center or physician. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If unconscious, place in recovery position and get medical attention immediately.
Skin contact	:	Clean shoes thoroughly before reuse. Get medical attention immediately. Wash clothing before reuse. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Remove contaminated clothing and shoes. Wash contaminated skin with soap and water. Call a poison center or physician. Chemical burns must be treated promptly by a physician. Continue to rinse for at least 10 minutes.
Ingestion	:	Get medical attention immediately. Never give anything by mouth to an unconscious person. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Loosen tight clothing such as a collar, tie, belt or waistband. Remove dentures if any. Do not induce vomiting unless directed to do so by medical personnel. Maintain an open airway. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Wash out mouth with water. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If unconscious, place in recovery position and get medical attention immediately. Chemical burns must be treated promptly by a physician.
Protection of first-aiders	:	It may be dangerous to the person providing aid to give mouth- tomouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.

4.2 Most important symptoms and effects, both acute and delayed

Potential	acute	health	effects
-----------	-------	--------	---------

Eye contact	:	Causes serious eye damage.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Causes severe burns.
Ingestion	:	May cause burns to mouth, throat and stomach.
-		

Over-exposure signs/symptoms

Eye contact

: redness

watering

		Adverse symptoms may include the following: pain
Inhalation	:	No specific data.
Skin contact	:	redness pain or irritation blistering may occur Adverse symptoms may include the following:
Ingestion	:	stomach pains Adverse symptoms may include the following:
4.3 Indication of any immediate	medical a	ttention and special treatment needed

Notes to physician	:	Treat symptomatically. Contact poison treatment specialist
		immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media :	Use an	extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal	:	No specific data.
decomposition products		
5.3 Advice for firefighters		
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Additional information	:	Not available.

Version: 1.0

Date of issue/Date of revision: 05.11.2020

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	Wear appropriate respirator when ventilation is inadequate. Do not touch or walk through spilled material. Evacuate surrounding areas. No action shall be taken involving any personal risk or without suitable training. Do not breathe vapor or mist. Put on appropriate personal protective equipment. Provide adequate ventilation. Keep unnecessary and unprotected personnel from entering.
For emergency responders	:	See also the information in "For non-emergency personnel". If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.
6.2 Environmental precautions	:	Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

6.3 Methods and materials for containment and cleaning up

Small spill Large spill	:	Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. The
		spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Wash spillages into an effluent treatment plant or proceed as follows. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Wear appropriate respirator when ventilation is inadequate. Empty containers retain product residue and can be hazardous. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Use only with adequate ventilation. Keep away from alkalis. Avoid release to the environment. Put on appropriate personal protective equipment (see Section 8). Do not ingest. Do not reuse container. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Advice on general occupational : Eating, drinking and smoking should be prohibited in areas where hygiene this material is handled, stored and processed. Remove

this material is handled, stored and processed. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Workers should wash hands and face before eating, drinking and smoking.

00.00.0000

7.2 Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Do not store in unlabeled containers. Separate from alkalis. Store locked up. Use appropriate containment to avoid environmental contamination. Keep container tightly closed and sealed until ready for use. Store in accordance with local regulations.

Seveso III Directive - Reporting thresholds

Named substances

Name	Notification and MAPP threshold	Safety report threshold
Hydrochloric acid	25 t	250 t

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
9i: Very toxic for the environment	100 t	200 t

7.3 Specific end use(s)

Recommendations		:	Not available.
Industrial sector specific	:		Not available.
solutions			

SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Version: 1.0 Date of issue/Date of revision: 05.11.2020 Date of previous issue:

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Hydrochloric acid	EU. Commission Directive 2000/39/EC of 8 June 2000 establishing
	a first list of indicative occupational exposure limit values in
	implementation of Council Directive 98/24/EC.(2000-06-01) Time
	Weighted Average (TWA) 8 mg/m3, 5 ppm
	EU. Commission Directive 2000/39/EC of 8 June 2000 establishing
	a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC.(2000-06-01)
	"shortterm exposure limit" means the maximum airborne
	concentration of a biological or chemical agent to which a worker may
	be exposed, (a) in any 15-minute period, (b) no more than four times
	during an eight hour work shift, and (c) with at least one hour between
	exposures 15 mg/m3, 10 ppm
	Ireland. 2002 Code of Practice for Safety, Health and Welfare at
	Work (Chemical Agents) Regulations 2001(1999-03-01) Notes:
	Indicative Occupational Exposure Limit Values are health based limits
	set under the Chemical Agents Directive 98/24/EC. The European
	Commission is advised on limits by its Scientific Committee on
	Occupational Exposure Limits (SCOEL). SCOEL evaluates the
	scientific information available on hazardous substances and makes
	recommendations for the establishment of an IOELV.IOELVs are
	listed in Directives, which Member States are obliged to implement by
	introducing national limits for the substances.
	Time Weighted Average (TWA) 7 mg/m3, 5 ppm
	Ireland. 2002 Code of Practice for Safety, Health and Welfare at
	Work (Chemical Agents) Regulations 2001(1999-03-01) Notes:
	Indicative Occupational Exposure Limit Values are health based limit
	set under the Chemical Agents Directive 98/24/EC. The European
	Commission is advised on limits by its Scientific Committee on
	Occupational Exposure Limits (SCOEL). SCOEL evaluates the
	scientific information available on hazardous substances and makes
	recommendations for the establishment of an IOELV.IOELVs are
	listed in Directives, which Member States are obliged to implement by
	introducing national limits for the substances.
	"short-term exposure limit" means the maximum airborn
	concentration of a biological or chemical agent to which a worker may
	be exposed, (a) in any 15-minute period, (b) no more than four time, during an eight hour work shift, and (c) with at least one hour between exposures 15 mg/m3, 10 ppm
	exposures to ing ins , to ppin

Recommended monitoring

:

If this product contains ingredients with exposure limits, personal, procedures workplace atmosphere or biological monitoring may be required

to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace

Version: 1.0

Date of issue/Date of revision: 05.11.2020 Date of previous issue: 00.00.0000

DNEL/DMEL Summary	:	atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required. Not available.
PNEC Summary	:	Not available.
8.2 Exposure controls		
Appropriate engineering controls	:	Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Use only with adequate ventilation.
Individual protection measures		
Hygiene measures	:	Wash contaminated clothing before reusing. Appropriate techniques should be used to remove potentially contaminated clothing. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		
Hand protection	:	It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision: 05.11.2020

Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Form	:	liquid [gel]
Color	:	Green.
Odor	:	Characteristic.
Odor threshold		Not available.
	•	
pH	•	<1 [Conc. (% w/w): 1.000 g/l]
Melting point/freezing point	:	Not available.
Initial boiling point and boiling	:	Not available.
range		
Flash point	:	Non-flammable.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Density	:	Not available
Bulk density	:	Not available
Burning time	:	Not available.
Burning rate	:	Not available.
Upper/lower flammability or	:	Lower: Not available. Upper:
explosive limits		Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1,072
Solubility(ies)	:	Not available.
Solubility in water	:	Not available.
Partition coefficient:	:	Not available.
noctanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Variana 10 Data diana	/D = 4 =	familian 05.11.2020 Data afarania

Version: 1.0

Date of issue/Date of revision: 05.11.2020

Viscosity	:	Dynamic: 770,000 mPa.s
Explosive properties Oxidizing properties	:	Kinematic: Not available. Not available. Not available.
9.2 Other information SADT Aerosol product	:	Not available
Type of aerosol Heat of combustion	:	Not available Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	chlorine-based bleaching agents Do not mix with :
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. metals alkalis Reactive or incompatible with the following materials:
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Remarks - Oral:	No applicable to	oxicity data		
Remarks - Inhalation:	No applicable to	No applicable toxicity data		
Remarks - Dermal:	No applicable toxicity data			
Remarks - Oral:	No applicable toxicity data			
Remarks - Inhalation:	No applicable toxicity data			

Version: 1.0 Date of issue/Date of revision: 05.11.2020

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830 Page:14/30

Remarks - Dermal:	No applicable toxicity data					
Remarks - Oral:	No applicable toxi	city data				
Remarks - Inhalation:	No applicable toxi	No applicable toxicity data				
Remarks - Dermal:	No applicable toxi	No applicable toxicity data				
Cetrimonium Chloride	· · · ·					
	LD50 Oral Rat - Female 450 mg/kg -					
Remarks - Inhalation:	No applicable toxicity data					
Remarks - Dermal:	No applicable toxicity data					
HHC-DOMESTOS-HELSINKI-LIME						
	LD50 Oral	Rat	> 5.000 mg/kg	-		

Conclusion/Summary

Very low toxicity to humans or animals. :

Acute toxicity estimates

Route	ATE value
Oral	21.600 mg/kg

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hydrochloric acid	Not relevant	Not relevant	0		-
Sulfamic Acid	Eyes - Severe irritant	Rabbit		24 hrs	-
	Skin - Mild irritant	Human		120 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	Eyes - Moderate irritant	Rabbit			-

Skin

Causes severe skin burns and eye damage. :

Eyes Respiratory

Causes serious eye damage. :

Non-irritating to the respiratory system. :

ensitization

	Product/ingredient name	Route of exposure	Species	Result
(Conclusion/Summary			

Skin

Not sensitizing

Version: 1.0

Date of issue/Date of revision: 05.11.2020

:

Respiratory	:	Not sensitizing
Mutagenicity		
Conclusion/Summary	:	Not applicable.
Carcinogenicity		
Conclusion/Summary	:	No additional remark.
<u>Reproductive toxicity</u>		
Conclusion/Summary	:	Not applicable.
Teratogenicity		
Conclusion/Summary	:	Not applicable.
Specific target organ toxicity (singl Not available.	e exp	<u>osure)</u>
Specific target organ toxicity (reper- Not available.	ated e	exposure)
<u>Aspiration hazard</u> Not available.		
Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact Inhalation	:	Causes serious eye damage. No known significant effects or critical hazards.
Skin contact	:	Causes severe burns.
Ingestion	:	May cause burns to mouth, throat and stomach.
Symptoms related to the physical, o	chemi	ical and toxicological characteristics
Eye contact	:	redness watering Adverse symptoms may include the following: pain
Inhalation	:	No specific data.
Skin contact	:	redness pain or irritation blistering may occur Adverse symptoms may include the following:
Ingestion	:	stomach pains Adverse symptoms may include the following:
Version: 1.0 Date of issue/	Date oj	

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Very low toxicity to humans or animals.
General Convinceministry	:	No known significant effects or critical hazards.
Carcinogenicity Mutagenicity	:	No known significant effects or critical hazards. No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hydrochloric acid			
Remarks - Acute - Fish:	No applicable tox	icity data	
Remarks - Acute - Aquatic invertebrates.:	No applicable tox	cicity data	
Remarks - Acute - Aquatic plants:	No applicable tox	cicity data	
Remarks - Chronic - Fish:	No applicable tox	cicity data	
Remarks - Chronic - Aquatic invertebrates.:	No applicable tox	icity data	
Sulfamic Acid			
Remarks - Acute - Fish:	No applicable tox	cicity data	
Remarks - Acute - Aquatic invertebrates.:	No applicable tox	cicity data	
Remarks - Acute - Aquatic plants:	No applicable tox	cicity data	
Remarks - Chronic - Fish:	No applicable tox	cicity data	

Version: 1.0 Date of

Remarks - Chronic -	No applicable toxicity data	
Aquatic invertebrates.:		
PEG-2 Oleamine		
	Acute $LC50 < 0.1 \text{ mg/l}$ Fish - Fish	96 h
	Fresh water	
Remarks - Acute - Fish:	Acute	
Remarks - Acute - Aquatic invertebrates.:	No applicable toxicity data	
	NT	
Remarks - Acute - Aquatic plants:	No applicable toxicity data	
Remarks - Chronic - Fish:	No applicable toxicity data	
Remarks - Chronic -	No applicable toxicity data	
Aquatic invertebrates.:		
Cetrimonium Chloride		
Remarks - Acute - Fish:	No applicable toxicity data	
Remarks - Acute - Aquatic	No applicable toxicity data	
invertebrates.:		
Remarks - Acute - Aquatic	No applicable toxicity data	
plants:		
Remarks - Chronic - Fish:	No applicable toxicity data	
Remarks - Chronic -	No applicable toxicity data	
Aquatic invertebrates.:	•	
O I /O		

Conclusion/Summary

: Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

2.2 I el sistence anu degladability		
Conclusion/Summary	:	The surfactants used in this mixture are readily biodegradable. The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the
		request of a detergent manufacturer.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Hydrochloric acid	0,25	-	
Sulfamic Acid	0,101	-	
Cetrimonium Chloride	3,23	160,00	

12.4 Mobility in soil

Soil/water partition coefficient : Not available. (KOC)

```
Version: 1.0
```

Date of issue/Date of revision: 05.11.2020

Mobility :	Mixture is highly soluble
12.5 Results of PBT and vPvB assessmen	
PBT :	Not available. P: Not available. B: Not available. T:
vPvB :	Not available. vP: Not available. vB:
12.6 Other adverse effects :	The substances used in this mixture are neither a PBT- or a vPvB substance

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

```
Product
```

Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	:	The classification of the product may meet the criteria for a hazardous waste.
Packaging		
Methods of disposal	:	The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	:	Empty containers or liners may retain some product residues. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. This material and its container must be disposed of in a safe way.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN3264	UN3264	UN3264	UN3264
14.2 UN proper shipping name	CORROSIVE LIQUID, ACIDIC INORGANIC N.O.S (Sulphamic acid, Hydrochloric acid)			
14.3 Transport hazard class(es)	Class 8: Corrosive substances.			
14.4 Packing group	III	III	III	III
14.5. Environmental hazards	No.	No.	No.	No.
Additional information	Tunnel code: (E)		Emergency schedules(EmS):FA, S-B	

14.6 Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV: None of the components are listed.

<u>Substances of very high concern</u>: None of the components are listed.

Other EU regulations

Europe inventory:Not determined.Industrial emissions (integrated
pollution prevention and
control) - AirNot listedVersion:1.0Date of issue/Date of revision:05.11.2020

Industrial emissions (integrated Not listed : pollution prevention and control) - Water

Product/ingredien	Carcinogenic	Mutagenic	Developmental	Fertility effects
t name	effects	effects	effects	

Aerosol dispensers

: Not applicable.

Seveso III Directive

This product is controlled under the Seveso Directive.

Named substances

Name
Hydrochloric acid

Danger criteria

Category
9i: Very toxic for the environment

National regulations

Remark	:	No additional remark.
International regulations		
Chemical Weapons Convention	:	Not listed
List Schedule I Chemicals		
Chemical Weapons Convention	:	Not listed
List Schedule II Chemicals		
Chemical Weapons Convention	:	Not listed
List Schedule III Chemicals		
15.2 Chemical Safety Assessment	:	Not available.

SECTION 16: Other information

Abbreviations and acronyms	Détergence et de for Soaps, Deter CLP = Classifica [Regulation (EC DNEL = Derived DMEL = Derived EUH statement = PBT = Persisten PNEC = Predicta RRN = REACH	xicity Estimate ion Internationale de la Savonne s Produits d'Entretien, Internati gents and Maintenance Products tion, Labelling and Packaging R No. 1272/2008] No Effect Level d Minimal Effect Level cLP-specific Hazard statement , Bioaccumulative and Toxic ed No Effect Concentration Registration Number rsistent and Very Bioaccumulative	onal Association Regulation
Version: 1.0 Date of issue/D	ate of revision: 05.11.20	20 Date of previous issue:	00.00.0000

Key literature references and:Evaluation method used for mixture classification: Calculationsources for datamethod.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Met. Corr. 1, H290	On basis of test data
Skin Corr./Irrit. 1, H314	On basis of test data
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H : H311 Toxic in contact with skin. **statements** H302 Harmful if swallowed.

H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H318 Causes serious eye damage. H319 Causes serious eye irritation. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H290 May be corrosive to metals. H335 May cause respiratory irritation. Full text of classifications Acute Tox. 3, H311: ACUTE TOXICITY: SKIN - Category 3 : [CLP/GHS] Acute Tox.Aquatic Acute 4, H302 1, H400: ACUTE TOXICITY: AQUATIC HAZARD (ACUTE): ORAL -Category 4 - Category 1 Aquatic Chronic 1, H410: AQUATIC HAZARD (LONG-TERM) - Category 1 Aquatic Chronic 3, H412: AQUATIC HAZARD (LONG-TERM) - Category 3 Eye Dam./Irrit. 1, H318: SERIOUS EYE DAMAGE/ EYE IRRITATION -Category 1 Eye Dam./Irrit. 2, H319: SERIOUS EYE DAMAGE/ EYE IRRITATION -Category 2 Skin Corr./Irrit. 1, H314: SKIN CORROSION/IRRITATION - Category 1 Skin Corr./Irrit. 1B, H314: SKIN CORROSION/IRRITATION - Category 1B Date of previous issue: 00.00.0000 Version: 1.0 Date of issue/Date of revision: 05.11.2020

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2015/830
Page:22/30

Skin Corr./Irrit. 2, H315: SKIN CORROSION/IRRITATION - Category 2
Met. Corr. 1, H290: CORROSIVE TO METALS - Category 1
STOT SE 2, H335: SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 2

Date of printing	:	05.11.2020
Date of issue/ Date of revision	:	05.11.2020
Date of previous issue	:	00.00.0000
Reason	:	Not applicable
Version	:	1.0

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

ANNEXES TO SAFETY DATA SHEET: EXPOSURE SCENARIOS FOR COMMUNICATION

Exposure Scenario related to HYDROGEN CHLORIDE (7647-01-0)

Exposure Sc	enario 1: Professional use of Cleaning and Ca	re pro	lucts
Use descriptor	Sectors of use:		
	SU22: Professional uses		
	Process categories:	1	
	PROC8a:		r of substance or preparation ng/discharging) from/ to vessels/ large ers at non-dedicated facilities
	PROC10:	Roller a	pplication or brushing
	PROC11:	Non ind	lustrial spraying
	PROC13:	Treatme	ent of articles by dipping and pouring
	Product categories: PC35: Washing and Cleaning Products (including solvent bas	ed produc	ts)
	Environmental release categories:		
	ERC8a	Wide di systems	spersive indoor use of processing aids in open
1.1. Exposure sce	enario		
1.2. Contributing	scenario controlling environmental exposure		
Amounts used			
Maximum daily si	te tonnage (kg/day)		No data available
Frequency and d	uration of use		
Emission days (da	ys/year)		Continuous exposure
Other operationa	l conditions affecting environmental exposure		
Release fraction to	air from process		No exposure assessment presented for the
Release fraction to	wastewater from process		environment. Substance will disassociate upon contact with water, the only effect is
Release fraction to soil from process (regional only)		the pH effect, therefore after passing throug the STP exposure is considered negligible and with no risk.	
Organizational m	neasures to prevent/limit release from site		
Ensure all waste w	vater is collected and treated via a WWTP.		
secondary treatme		ewater tre	atment plant that incorporates both primary and
	prevent soil / water pollution caused by leaks.		
	scenarios controlling worker exposure		
Product characte	eristics		
Concentration in p	preparations:		Covers percentage substance in the product up to 40 %
Frequency and d			
Version	n: 1.0 Date of issue/Date of revision: 05.11.2020	Dat	e of previous issue: 00.00.0000

Operational conditions affecting workers exposure Place of Use: Indoor use Technical and organizational measures to prevent/limit releases, dispersion and exposure PROCSa: Clear transfer lines prior to de-coupling. PROCSa: Clear transfer lines prior to de-coupling. PROCSa: ProClis: Provide extraction ventilation at points where emissions occur (Efficiency: 90 %). PROCSa: Handle substance within a predominantly closed system provided with extract ventilation (Efficiency: 90 %). PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). PROC13: Envice entrants of prevent/minimize exposures PROC13: Envice entrants of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear chemically resistant gloves. PROC11: Wear suitable gloves tested to EN374. PROC11: Wear suitable gloves tested to EN374. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear chemically resistant gloves. Vear a half face respirator conforming to EN140 Type A filter or better. PROC11: Wo not carry out the operation conforming to EN140 Type A filter or better. Other informatio	Duration of Exposure:	Covers daily exposures up to 8 hours. PROC11: Avoid carrying out operation for more than 15 minutes (without respiratory protection).
Technical and organizational measures to prevent/limit releases, dispersion and exposure PROC8a: Clear transfer lines prior to de-coupling. PROC8a: PROC11: Provide extraction ventilation at points where emissions occur (Efficiency: 90 %). PROC8a: Handle substance within a predominantly closed system provided with extract ventilation (Efficiency: 90 %). PROC11: Provide a good standard of controlled ventilation (10 to 15 air changes per hour) (Efficiency: 90 %). PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). Provide basic employee training to prevent/minimize exposures PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC11: 1, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear suitable conforming to EN140 Type A filter or better. PROC11: Do not carry out the operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-speci	Operational conditions affecting workers exposure	
 PROC8a: Clear transfer lines prior to de-coupling. PROC8a: Handle substance within a predominantly closed system provided with extract ventilation (Efficiency: 90 %). PROC8a: Handle substance within a predominantly closed system provided with extract ventilation (Efficiency: 90 %). PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). Provide basic employee training to prevent/minimize exposures PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC11: User a half face respirator conforming to EN140 Type A filter or better. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. POHer information related to RMM Risk management measures are based on qualitative risk characterisation. 14. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the Co and RMM are within the boundaries set by the ES. AddItional good practice advice. Obligations according to Article 37(4) of	Place of Use:	Indoor use
PROC8a, PROC11: Provide extraction ventilation at points where emissions occur (Efficiency: 90 %). PROC8a: Handle substance within a predominantly closed system provided with extract ventilation (Efficiency: 90 %). PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent/minimize exposures PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Cother information related to RMM Risk management measures are based on qualitative risk characterisation. I.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetor.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	Technical and organizational measures to prevent/limit releases, dispersion and expose	ıre
PROC8a: Handle substance within a predominantly closed system provided with extract ventilation (Efficiency: 90 %). PROC10: Provide a good standard of controlled ventilation (10 to 15 air changes per hour) (Efficiency: 90 %). PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). Provide basic employee training to prevent/minimize exposures PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC10: 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operating to qualitative risk characterisation. 14. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.eceto.corg/tra Only properly trained persons hall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	PROC8a: Clear transfer lines prior to de-coupling.	
 PROC10: Provide a good standard of controlled ventilation (10 to 15 air changes per hour) (Efficiency: 90 %). PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). Provide basic employee training to prevent/minimize exposures PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. POC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. POC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent l	PROC8a, PROC11: Provide extraction ventilation at points where emissions occur (Efficien	ncy: 90 %).
PROC13: Carry out in a vented booth provided with laminar airflow. Allow time for product to drain from workpiece. Automate activity where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). Provide basic employee training to prevent/minimize exposures PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear shaft face respirator conforming to EN140 Type A filter or better. PROC1: So not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. PROC1: bo not carry out the operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.eceto.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations	PROC8a: Handle substance within a predominantly closed system provided with extract ver	ntilation (Efficiency: 90 %).
 where possible. PROC13: Provide extract ventilation to material transfer points and other openings (Efficiency: 90 %). Provide basic employee training to prevent/minimize exposures PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear suitable coveralls to prevent exposure to the Skin. Use suitable eye protection. Wear suitable coveralls to prevent exposure to the Skin. Use suitable eye protection. Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 14. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Ohy properly trained persons shall make use of scaling methods while checking whether the doc and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply 		
Provide basic employee training to prevent/minimize exposures PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		act to drain from workpiece. Automate activity
PROC13: Ensure minimization of manual phases. Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	PROC13: Provide extract ventilation to material transfer points and other openings (Efficien	ncy: 90 %).
Conditions and measures related to personal protection, hygiene and health evaluation Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	Provide basic employee training to prevent/minimize exposures	
 Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection. Wear chemically resistant gloves. PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply 	PROC13: Ensure minimization of manual phases.	
 Wear chemically resistant gloves. PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply 	Conditions and measures related to personal protection, hygiene and health evaluation	l
 PROC10, 11, 13: Wear suitable gloves tested to EN374. PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply 	Wear suitable coveralls to prevent exposure to the skin. Use suitable eye protection.	
PROC11: Wear a half face respirator conforming to EN140 Type A filter or better. PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	Wear chemically resistant gloves.	
PROC11: Do not carry out the operation for more than 15 min without respiratory protection. Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	PROC10, 11, 13: Wear suitable gloves tested to EN374.	
Wear a half face respirator conforming to EN140 Type A filter or better. Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	PROC11: Wear a half face respirator conforming to EN140 Type A filter or better.	
Other information related to RMM Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		n.
Risk management measures are based on qualitative risk characterisation. 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	Wear a half face respirator conforming to EN140 Type A filter or better.	
 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply 	Other information related to RMM	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	Risk management measures are based on qualitative risk characterisation.	
sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply	1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
 measures. Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply 		
should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		
For further information on the assessment method, see: http://www.ecetoc.org/tra Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		
the OC and RMM are within the boundaries set by the ES. Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply		
do not apply		
Assumes a good basic standard of occupational hygiene is implemented.		
	Assumes a good basic standard of occupational hygiene is implemented.	

Exposure Scenario related to CETRIMONIUM CHLORIDE (112-02-7)

Use descriptor	Sectors of use:			
	SU22: Professional uses			
	Process categories:			
	PROC8a:	Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at non-dedicated facilities		
	PROC10:	Roller application or brushing		
	PROC11:	Non industrial spraying		
	PROC13:	Treatment of articles by dipping and pouring		
	Product categories: PC35: Washing and Cleaning Products (inc	uding solvent based products)		
	Environmental release categories:			
	ERC8a	Wide dispersive indoor use of processing aids in open systems		
1.1. Exposure sc	enario			
1.2. Contributin	g scenario controlling environmental exposu	re		
Amounts used				
Maximum daily s	ite tonnage (kg/day)	No data available		
Frequency and d	luration of use			
Emission days (da	ays/year)	No data available		
Other operation	al conditions affecting environmental exposu	re		
Release fraction t	o air from process			
Release fraction t	o wastewater from process	No data available		
Release fraction t	o soil from process (regional only)			
Organizational r	neasures to prevent/limit release from site			
Dispose of waste	product or used containers according to local re-	gulations.		
1.3. Contributin	g scenarios controlling worker exposure			
Product charact	eristics			
Concentration in	preparations:	PROC 8a: Limit the substance content in the product to 25%.PROC 10, PROC 11, PROC 13: Limit the substance content in the product to 5%.		
Frequency and o	duration of use	·		
Duration of Expo	sure:	Covers daily exposures up to 8 hours.		
Operational con	ditions affecting workers exposure	· · · ·		

Date of issue/Date of revision: 05.11.2020

Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
PROC 10: Local exhaust ventilation - efficiency of at least 80%	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.	
1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
Environment:	
Required removal efficiency for wastewater can be achieved using onsite/offsite	
technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either	
alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1),	
additional RMMs or a site-specific chemical safety assessment is required.	
Health:	
Predicted exposures are not expected to exceed the DN(M)EL when the risk management	
measures/operational conditions outlined in section 2 are implemented.	
Where other risk management measures/operational conditions are adopted, then users	
should ensure that risks are managed to at least equivalent levels.	
Guidance is based on assumed operating conditions which may not be applicable to all	
sites; thus, scaling may be necessary to define appropriate site-specific risk management	
measures.	

Exposure Scenario related to PEG-2 OLEAMINE (25307-17-9)

Exposure Scenario 1: Professional use of Cleaning and Care products					
Use descriptor	Sectors of use:				
	SU22: Professional uses				
	Process categories:				
			sfer of substance or preparation ging/discharging) from/ to vessels/ large iners at non-dedicated facilities		
	PROC10:	Roller	application or brushing		
	PROC11:	Non industrial spraying			
	PROC13:	Treatm	ent of articles by dipping and pouring		
	Product categories: PC35: Washing and Cleaning Products (including solvent based products)				
	Environmental release categories:				
	ERC8a	Wide of system	lispersive indoor use of processing aids in open s		
1.1. Exposure sce	nario				
1.2. Contributing	scenario controlling environmental exposure				
Amounts used					
Maximum daily si	te tonnage (kg/day)		20 kg/day		
Frequency and du	uration of use				
Emission days (days/year)			No data available		
Environmental fa	ctors not influenced by risk management				
Local freshwater dilution factor			10		
Local marine water dilution factor			100		
Other operationa	l conditions affecting environmental exposure				
Release fraction to	air from process		0%		
Release fraction to wastewater from process			100 % (maximum concentration/release value to freshwater $< 0.02 \ \mu g/l)$		
Release fraction to	soil from process (regional only)		0%		
Organizational m	easures to prevent/limit release from site				
Water : Ensure all Soil : Soil emission Waste treatment :	controls are not applicable as there is no direct release to air. waste water is collected and treated via a WWTP. n controls are not applicable as there is no direct release to soil. Do not apply industrial sludge to natural soils. product or used containers according to local regulations.				
1.3. Contributing	scenarios controlling worker exposure				
Product characte	ristics				
Concentration in p	reparations:		Covers percentage substance in the product up to 5 $\%$		
Frequency and d	uration of use				

Duration of Exposure:	Covers daily exposures up to 8 hours (unless stated differently).			
Operational conditions affecting workers exposure				
Place of Use:	Indoors			
Technical and organizational measures to prevent/limit releases, dispersion and expos	ure			
Provide adequate information, instruction and training for operators.				
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				
Avoid splashing.				
Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.				
Assumes a good basic standard of occupational hygiene is implemented.				
Provide extraction ventilation at points where emissions occur.				
Supervise workers to make sure that operational conditions are followed and risk management measures properly used.				
Horizontal or downward spraying.				
Does not cover spraying under high pressure (air blasting).				
Maximal spray rate: 3 L/min per operator				
Conditions and measures related to personal protection, hygiene and health evaluation	n			
Wear suitable gloves (tested to EN374), coverall and eye protection.				
1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES				
For a given contributing scenario, several risk management measures can be proposed. It is your responsibility to select the configuration that best suits your activity.				

Exposure Scenario related to SULFAMIC ACID (5329-14-6)

Use descriptor	Sectors of use:				
	SU22: Professional uses				
	Process categories:				
	PROC8a:		Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at non-dedicated facilities		
	PROC10:	PROC10: Roller application or brushing			
	PROC11:		Non industrial spraying		
	PROC13:		Treatment of articles by dipping and pouring		
	Product categories: PC35: Washing and Cleaning Products (including solvent based products) Environmental release categories:				
					ERC8a
	1.1. Exposure sc	enario			
1.2. Contributin	g scenario controlling environmental expo	osure			
Amounts used					
Maximum daily s	ite tonnage (kg/day)		6 kg/day		
Frequency and d	luration of use				
Emission days (da	ays/year)		No data available		
Environmental f	actors not influenced by risk management	t			
Local freshwater dilution factor		10			
Local marine wat	ocal marine water dilution factor		100		
Other operation	al conditions affecting environmental expo	osure			
STP			Yes, municipal		
STP sludge treatm	nent		Controlled application of sewage sludge to agricultural soil		
River flow rate			18000 m ³ /d		
	e treatment plant discharge		2000000 L/d		
Organizational r	neasures to prevent/limit release from site				
No data available					
1.3. Contributin	g scenarios controlling worker exposure				
Product charact	eristics				
Concentration in	oncentration in preparations:		PROC11: Covers percentage of substance in the product up to 5%.		
Frequency and o	luration of use				
Duration of Expo			Covers daily exposures < 8 hours		

Place of Use:	Indoors				
Technical and organizational measures to prevent/limit releases, dispersion and exposure					
<u>Open systems</u>					
Ensure operatives are trained to minimise exposures.					
Local exhaust ventilation					
Provide a basic standard of general ventilation (1 to 3 air changes per hour).					
Inhalation - minimum efficiency of 0 %					
For further specification, refer to section 8 of the SDS.					
Conditions and measures related to personal protection, hygiene and he	alth evaluation				
Wear suitable gloves tested to EN374.					
Dermal - minimum efficiency of 90 %					
For further specification, refer to section 8 of the SDS.					
1.4. Guidance to DU to evaluate whether he works inside the boundaries	s set by the ES				
No data available					
Additional good practice advice. Obligations according to Article 37(4)	of REACH do not apply				
Wear suitable coveralls to prevent exposure to the skin.					
Ensure regular inspection, cleaning and maintenance of equipment and mach	ines.				
Keep good industrial hygiene.					